

## T93F Industrial Grade Flat Tip



The T93F uses the same mega-hard carbide as the T93R series. Each tip comes complete with 1/8" gasket. Chart below lists all available sizes. 5000 PSI (345 BAR)

**Part No. 205-xxx**

## T93F INDUSTRIAL GRADE FLAT TIP GUARD

The T93F Safety Guard fits all major manufacturers airless spray guns. Flat tips "lock" in to cavity for positive alignment. 5000 PSI (345 BAR) Nut Size 7/8"

**Part No. 205-999**



## Industrial Flat Tip Sizing Chart

Orifice Size (inches)	Fan Width - Inches								Flow Rate (gpm)
	4" - 6"	6" - 8"	8" - 10"	10" - 12"	12" - 14"	14" - 16"	16" - 18"	18" - 20"	
.009"	209	309	409	509	609				.09
.011"	211	311	411	511	611				.12
.013"	213	313	413	513	613	713	813		.18
.015"	215	315	415	515	615	715	815		.24
.017"	217	317	417	517	617	717	817	917	.31
.018"	219	319	419	519	619	719	819	919	.38
.021"	221	321	421	521	621	721	821	921	.47
.023"	223	323	423	523	623	723	823	923	.57
.025"	225	325	425	525	625	725	825	925	.67
.027"		327	427	527	627	727	827	927	.77
.029"		329	429	529	629	729	829	929	.90
.031"		331	431	531	631	731	831	931	1.03
.033"		333	433	533	633	733	833	933	1.17
.035"		335	435	535	635	735	835	935	1.31
.039"		339	439	539	639	739	839	939	1.63
.043"		343	443	543	643	743	843	943	1.93
.045"			445	545	645	745			2.17
.047"			447	547	647	747			2.36
.049"			449	549	649	749			2.57
.051"			451	551	651	751			2.79
.053"			453	553	653	753			3.00
.055"			455	555	655	755			3.25
.063"			463	563	663	763			4.26
.065"			465	565	665	765			4.43

Example : For a tip with a .017" orifice and a 10" - 12" fan pattern, order 205-517 T93F Flat Tip. Fan width of a spray pattern is measured at 12" from the surface.

Recommended Tip Sizes for Typical Coatings				
Stain or Lacquer	Oil Base Paint	Latex Paint	Heavy Latex	Elastomeric/Blockfiller